

Dholakia, Umesh

From: Dholakia, Umesh
Sent: Thursday, February 28, 2013 9:01 AM
To: 'Angel Berrios'
Cc: beatriz.rivera@essroc.com; Steve Cullen
Subject: RE: Essroc Answer to Request for Information

Thanks.

What is the heat balance? That is, what is the MMBTU/ton of clinker produced number for ESSROC? Is it [1980000 MMBTU/241,000 tons]? The average is around 1800 Btu/lb of clinker.....that I have seen.

From: Angel Berrios [<mailto:Angel.Berrios@erm.com>]
Sent: Wednesday, February 27, 2013 6:33 PM
To: Dholakia, Umesh
Cc: beatriz.rivera@essroc.com; Steve Cullen
Subject: Essroc Answer to Request for Information

Umesh,

The following are the answer to your questions.

The up to 35 percent of AF substitution represent the substitution of the current fuels used at Essroc. The approach that we would like to use is adding the use of a new fuel to the process.

The use of up to 70,000 tons of alternative fuel per year represent a substitution of approximately 32,000 tons of coal per year or 22,000 tons of oil. The total amount of clinker that can be produced is up to 241,305 ton of clinker per year which is below the current permitted limit.

1. Please justify ESSROC's proposed 35% (70,000 tons/year) limit with Heat Input numbers- MMBtu/year or better.

The idea is to maintain the same requirements established in the permits issued to Essroc for coal and oil. The approach used in the construction and Title V permit is to establish the amount of fuel that is need for the production of clinker. As stated above the plans are to substitute up to 35 percent of the current fuels used at the facility. The following information will provide you with the percent of substitution of fossil fuel.

Type Fuel	Fuel	Total (ton/year)	Average Heat Content (MMBtu/ton)	Total Heat Input for Clinker Production (MMBTU/year)	Percent Substitution
Coal		90000	22	1980000	35%
Biomass		70000	10	700000	

Type Fuel	Fuel	Total (ton/year)	Average Heat Content (MMBtu/ton)	Total Heat Input for Clinker Production (MMBTU/year)	Percent Substitution
Oil		69657	34	2368338	30%

Biomass	70000	10	700000	
---------	-------	----	--------	--

2. Does ESSROC keep track of the coal, oil, and tire's heat contents?

Yes, Essroc maintain records of each batch of coal or oil received.

3. Also, ESSROC proposes to stack test to verify the emission factors used in this non-app demonstration- that is my understanding.

Yes, a stack test will be performed to verify and emission factors.

If you have any more questions please let me know.

Angel

Angel O. Berríos Silvestre, P.E.

Engineer Consultant - Air Resources
Environmental Resources Management
250 Ponce de Leon Ave.
City Tower, Suite 900
San Juan, P.R. 00918

telephone: 787-622-0808

cel.: 787-383-2696

ESSROC SAN JUAN INC.
SAMPLE CALCULATIONS AVERAGE HEAT TO PRODUCE CLINKER

COAL: Permit limit: 90,000 tons coal/ year Average Heat Content: 22 MM Btu/ton coal

$$\frac{90000 \text{ ton coal}}{\text{year}} \times \frac{22 \text{ MM Btu}}{\text{ton coal}} = 1980000 \text{ MM Btu year}$$

The estimated heat to produce a pound of clinker using coal is the following:

$$\frac{1980000 \text{ MM Btu}}{\text{year}} \times \frac{\text{year}}{682550 \text{ ton clinker}} = \frac{2.90 \text{ MM Btu}}{\text{ton clinker}} \times \frac{1.00\text{E}+05 \text{ Btu}}{1 \text{ MM Btu}} \times \frac{1 \text{ ton}}{2000 \text{ lb}} = 1,450.44 \text{ Btu lb clinker}$$

BIOMASS: Permit Limit Request: 70,000 tons biomass/year Average Heat Content: 10 MM Btu/ton biomass

$$\frac{70000 \text{ ton biomass}}{\text{year}} \times \frac{10 \text{ MM Btu}}{\text{ton biomass}} = 700000 \text{ MM Btu year}$$

The estimated heat to produce a pound of clinker using biomass is the following:

$$\frac{700000 \text{ MM Btu}}{\text{year}} \times \frac{\text{year}}{241305 \text{ ton clinker}} = \frac{2.90 \text{ MM Btu}}{\text{ton clinker}} \times \frac{1.00\text{E}+05 \text{ Btu}}{1 \text{ MM Btu}} \times \frac{1 \text{ ton}}{2000 \text{ lb}} = 1,450.45 \text{ Btu lb clinker}$$

Used Oil: Permit Limit: 69657 tons of Used Oil/year Average Heat Content: 34MM Btu/ton Used Oil

$$\frac{69657 \text{ tons used oil}}{\text{year}} \times \frac{34 \text{ MM Btu}}{\text{ton biomass}} = 2368338 \text{ MM Btu year}$$

The estimated heat to produce a pound of clinker using used oil is the following:

$$\frac{2368338 \text{ MM Btu}}{\text{year}} \times \frac{\text{year}}{682550 \text{ ton clinker}} = \frac{3.47 \text{ MM Btu}}{\text{ton clinker}} \times \frac{1.00\text{E}+05 \text{ Btu}}{1 \text{ MM Btu}} \times \frac{1 \text{ ton}}{2000 \text{ lb}} = 1,734.92 \text{ Btu lb clinker}$$

Dholakia, Umesh

From: Angel Berrios [Angel.Berrios@erm.com]
Sent: Wednesday, February 27, 2013 6:33 PM
To: Dholakia, Umesh
Cc: beatriz.rivera@essroc.com; Steve Cullen
Subject: Essroc Answer to Request for Information

Umesh,

The following are the answer to your questions.

The up to 35 percent of AF substitution represent the substitution of the current fuels used at Essroc. The approach that we would like to use is adding the use of a new fuel to the process.

The use of up to 70,000 tons of alternative fuel per year represent a substitution of approximately 32,000 tons of coal per year or 22,000 tons of oil. The total amount of clinker that can be produced is up to 241,305 ton of clinker per year which is below the current permitted limit.

1. Please justify ESSROC's proposed 35% (70,000 tons/year) limit with Heat Input numbers- MMBtu/year or better.

The idea is to maintain the same requirements established in the permits issued to Essroc for coal and oil. The approach used in the construction and Title V permit is to establish the amount of fuel that is need for the production of clinker. As stated above the plans are to substitute up to 35 percent of the current fuels used at the facility. The following information will provide you with the percent of substitution of fossil fuel.

Type Fuel	Total Fuel (ton/year)	Average Heat Content (MMBtu/ton)	Total Heat Input for Clinker Production (MMBTU/year)	Percent Substitution
Coal	90000	22	1980000	35%
Biomass	70000	10	700000	

Type Fuel	Total Fuel (ton/year)	Average Heat Content (MMBtu/ton)	Total Heat Input for Clinker Production (MMBTU/year)	Percent Substitution
Oil	69657	34	2368338	30%
Biomass	70000	10	700000	

2. Does ESSROC keep track of the coal, oil, and tire's heat contents?

Yes, Essroc maintain records of each batch of coal or oil received.

3. Also, ESSROC proposes to stack test to verify the emission factors used in this non-app demonstration- that is my understanding.

Yes, a stack test will be performed to verify and emission factors.

If you have any more questions please let me know.

Angel

Angel O. Berríos Silvestre, P.E.

Engineer Consultant - Air Resources
Environmental Resources Management
250 Ponce de Leon Ave.
City Tower, Suite 900
San Juan, P.R. 00918

telephone: 787-622-0808

cel.: 787-383-2696

